

154L SPECIALTY ALKYLATE

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	154L SPECIALTY ALKYLATE	
Synonyms	Specialty Alkylate Bottoms	
Use	Industrial use, Mining, Oilfield Drilling	
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)	
Address	12120 Wickchester Lane Houston TX 77079	
Telephone	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424-9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(337) 494-5142
	SDS and Product Information (8:00am-4:30pm CST)	(281) 588-3491
	Health and Safety Information (7:30am-4:00pm CST)	(281) 588-3492
E-mail address	SasolElectronicSDS@us.sasol.com	

SECTION 2 HAZARDS IDENTIFICATION

Not a hazardous substance or mixture according to OSHA HCS 2012.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
Benzene, mono-C10-13-alkyl derivs., distn. residues	84961-70-6	100

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

Eye contact	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash contaminated clothing before re-use.
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.
Ingestion	If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

154L SPECIALTY ALKYLATE

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Spontaneous combustion can occur should the product come into contact with hot fiber glass or mineral fiber insulations (e.g. in case of leakages), especially when exposed to atmospheric oxygen (e.g. removal of insulation panels). NFPA Class IIIB combustible liquid.

Suitable extinguishing media Water spray or fog, foam, dry chemical, CO₂.

Protective equipment and precautions for firefighters In the event of fire and/or explosion do not breathe fumes. Wear self-contained breathing apparatus for firefighting if necessary.

Further information Keep containers and surroundings cool with water spray. Do not use a solid water stream as it may scatter and spread fire. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Ventilate the area. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Ensure all equipment is electrically grounded before beginning transfer operations. Keep away from sources of ignition - No smoking. Keep container tightly closed. The use of foam glass as an insulating material can reduce the risk of such spontaneous combustion. Insulation material soaked with the product must be replaced with new insulation material as soon as possible.

Storage/Transport pressure Ambient

Load/Unload temperature Ambient

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Air contaminant levels should be controlled below the PEL or TLV for this product (see Exposure Guidelines). Provide adequate ventilation. Use explosion-proof electrical/ ventilating/ lighting/ equipment.

154L SPECIALTY ALKYLATE

PERSONAL PROTECTIVE EQUIPMENT

Eyes Safety glasses with side-shields

Skin Wear suitable protective clothing, gloves and eye/face protection.

Inhalation Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

Contains no substances with occupational exposure limit values.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

Colour light brown oily

Form liquid

Odour Hydrocarbons

Odour Threshold No data available

Flash point 199 °C, 390 °F; COC;

Flammability Upper explosion limit: No data available

Lower explosion limit: No data available

Boiling point/boiling range 312 - 386 °C, 594 - 728 °F;

Melting point/range -16.6 - -11 °C, 2 - 12 °F;

Auto-ignition temperature 357 °C, 675 °F;

Decomposition temperature No data available;

Flammability (solid, gas) No data available

Vapour pressure 3.6 mm Hg @ 21 °C, 70 °F;

Vapour density None.

154L SPECIALTY ALKYLATE

Density	0.87 g/cm ³ @ 16 °C, 60 °F;
Specific gravity	No data available
Water solubility	insoluble
Viscosity	1872 cSt @ -40 °C, -40 °F;
pH	No data available
Evaporation rate	No data available
Partition coefficient: n-octanol/water	No data available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Conditions to avoid	Direct heating, dirt, chemical contamination, sunlight, UV or ionising radiation. Extremes of temperature and direct sunlight.
Hazardous decomposition products	No decomposition if stored normally. Stable under normal conditions. Use at elevated temperatures can lead to thermal decomposition and the formation of low-boiling and high-boiling secondary products (e.g. hydrocarbons). During removal of low-boiling decomposition products from the system, appropriate risk management measures for flammable liquids must be applied.
Materials to avoid	Strong oxidizing agents
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	LD50 Rabbit: > 2,000 mg/kg
Acute inhalation toxicity	No data available
Acute oral toxicity	LD50 Rat: > 5,000 mg/kg
Skin corrosion/irritation	Primary irritation (Rabbit): 0.8 (Max. score is 8.0.)

154L SPECIALTY ALKYLATE

Serious eye damage/eye irritation	Primary irritation (Rabbit): 3.7 (Max. score is 110.)
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	Genotoxicity in vitro: No data available Genotoxicity in vivo: No data available Assessment Mutagenicity: No data available
Reproductive toxicity	Reproductive toxicity: No data available Assessment Reproductive toxicity: No data available Teratogenicity: No data available Assessment teratogenicity: No data available
STOT - single exposure	No data available
STOT - repeated exposure	No data available
Aspiration toxicity	No data available
Carcinogenicity	Assessment carcinogenicity: Contains no ingredient listed as a carcinogen

SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity	Aquatic toxicity is unlikely due to low solubility.
Toxicity to fish	Aquatic toxicity is unlikely due to low solubility., Expected to be found on solid surfaces such as sediments, soils and biosludges and not in the water., (Based on analogy with similar products).
Toxicity to aquatic	No data available

154L SPECIALTY ALKYLATE

invertebrates**Toxicity to algae** No data available**Chronic toxicity to fish** No data available**Chronic toxicity to aquatic invertebrates** No data available**Biodegradation** Biodegradable, but at slow rates.
Due to its low solubility in water, large amounts can be eliminated by separators for oil or fat.**Bioaccumulative potential** No data available**Mobility in soil** No data available**Other adverse effects** No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Code Any unused product or empty containers may be disposed of as non-hazardous in accordance with state and federal requirements. Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification. If the resulting material is determined to be hazardous, please dispose in accordance with state and federal (40 CFR 262) hazardous waste regulations.**Disposal methods** Dispose of only in accordance with local, state, and federal regulations.**Empty containers.** Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

DOT not regulated**IATA** not regulated**IMDG** not regulated

154L SPECIALTY ALKYLATE

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks No data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA Inventory Listing

Components

Benzene, mono-C10-13-alkyl derivs., distn. residues

CAS-No.

84961-70-6

SARA 302 Status

Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CAS-No.

Weight percent

SARA 311/312 Classification

SARA 313 Chemical

Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

CAS-No.

Weight percent

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

none

Reportable Quantity

Weight percent

INTERNATIONAL REGULATIONS

WHMIS Classification

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).

European Union

Classification according to Regulation (EU) 1272/2008.

Aspiration hazard, Category 1

Australia. Inventory of Chemical Substances (AICS)

Listed

Japan. Inventory of Existing and New Chemical Substances (ENCS)

Listed

Japan. ISHL - Inventory of Chemical Substances

Not listed

Canada. Domestic Substances List (DSL) Inventory

Not listed

Canada. Non-Domestic Substance Listing (NDSL)

Listed

154L SPECIALTY ALKYLATE

Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Not listed
Korea. Existing Chemicals Inventory (KECI)	Not listed
China. Inventory of Existing Chemical Substances (IECSC)	Listed
Mexico	Not listed
New Zealand. Inventory of Chemical Substances	Not listed
Switzerland	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65
Components
 none

CAS-No.

SECTION 16 OTHER INFORMATION

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	1	1	0
NFPA	1	1	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
