

n-Butanol

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name	n-Butanol	
Synonyms	Butyl Alcohol, 1-Butanol	
Use	Fuel additive, Industrial use, Intermediate, Oilfield, Paint and Coatings, Process/Extraction Solvent, Raw material for chemical processes, Raw material for industry, Solvent	
Company	Sasol Chemicals (USA) LLC (an affiliate of Sasol Chemicals North America LLC)	
Address	12120 Wickchester Lane Houston TX 77079	
Telephone	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424-9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(337) 494-5142
	SDS and Product Information (8:00am-4:30pm CST)	(281) 588-3491
	Health and Safety Information (7:30am-4:00pm CST)	(281) 588-3492
E-mail address	SasolElectronicSDS@us.sasol.com	

SECTION 2 HAZARDS IDENTIFICATION

OSHA/GHS Hazards	Flammable liquids	Category 3
	Acute toxicity (Oral)	Category 4
	Serious eye damage	Category 1
	Skin irritation	Category 2
	Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)
	Specific target organ toxicity - single exposure	Category 3 (Resp. irritation)

LABEL ELEMENTS**Hazard symbols****Signal word** Danger

Hazard statements H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H315 Causes skin irritation.

n-Butanol

H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/ eye protection/ face protection.
P264 Wash skin thoroughly after handling.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Response P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction.
P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P330 Rinse mouth.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Storage P403 + P405 + P235 Store locked up in a well-ventilated place. Keep cool.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

<u>Components</u>	<u>CAS-No.</u>	<u>Weight percent</u>
1-Butanol	71-36-3	>=99

See Section 8 for Exposure Guidelines and Section 15 for Regulatory Classifications.

SECTION 4 FIRST AID MEASURES

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

n-Butanol

- Skin contact** Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. When symptoms persist or in all cases of doubt seek medical advice. Wash contaminated clothing before re-use.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of shortness of breath, give oxygen. Call a physician immediately.
- Ingestion** If swallowed, call a poison control centre or doctor immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

SECTION 5 FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Fire/explosion Flash back possible over considerable distance. NFPA Class II combustible liquid.

Suitable extinguishing media Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO₂)

Protective equipment and precautions for firefighters Wear self-contained breathing apparatus and protective suit. Keep containers and surroundings cool with water spray.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Methods and materials for containment and cleaning up Evacuate personnel to safe areas. Remove all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Do not flush into surface water or sanitary sewer system.

Spill precautions Material can create slippery conditions.

SECTION 7 HANDLING AND STORAGE

Safe handling advice Ensure all equipment is electrically grounded before beginning transfer operations.

Storage/Transport pressure Ambient

Load/Unload temperature Ambient

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING MEASURES

Ensure adequate ventilation, especially in confined areas.

n-Butanol

PERSONAL PROTECTIVE EQUIPMENT

Eyes Wear as appropriate: Goggles, Face-shield

Skin Wear suitable protective clothing, gloves and eye/face protection.

Inhalation Respiratory protection is normally not required except in emergencies or when conditions cause excessive airborne levels of mists or vapors. Use NIOSH approved respiratory protection.

EXPOSURE GUIDELINES

Components Exposure limit(s)

1-Butanol OSHA PEL (Permissible Exposure Limit) 100 ppm 300 mg/m³
ACGIH TLV (8-hour) 20 ppm

*Skin Hazard: Skin exposure should be prevented or reduced to control skin absorption.

PEL= Permissible Exposure Limits
TLV= Threshold Limit Value
EL= Excursion Limit

TWA= Time Weighted Average (8 hr.)
STEL= Short Term Exposure Limit (15 min.)
WEEL= Workplace Environmental Exposure Level

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid;

Colour colourless

Form liquid

Odour sweet pungent

Odour Threshold No data available

Flash point 38 °C, 100 °F; ASTM D 93;

Flammability Upper explosion limit: 11.2 %(V)
Lower explosion limit: 1.4 %(V)

Boiling point/boiling range 117 °C, 242 °F;

Melting point/range -89 °C, -128 °F;

Auto-ignition temperature 343 °C, 649 °F;

Decomposition temperature No data available

n-Butanol

Flammability (solid, gas)	No data available
Vapour pressure	4.5 mm Hg @ 25 °C, 78 °F;
Vapour density	2 - 3
Density	0.805 g/cm ³ @ 27 °C, 80 °F;
Specific gravity	No data available
Water solubility	7.8 g/100g partly soluble
Viscosity	4 cSt @ 20 °C, 68 °F;
pH	No data available
Evaporation rate	No data available
Partition coefficient: n-octanol/water	No data available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Conditions to avoid	Keep away from heat and sources of ignition.
Hazardous decomposition products	Combustion products include carbon dioxide, carbon monoxide and possibly other unidentified organic compounds.
Materials to avoid	Can react with strong oxidizers, inorganic acids, and halogens.
Hazardous polymerisation	None.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute dermal toxicity	LD50 Rabbit: 2,000 - 5,300 mg/kg
Acute inhalation toxicity	LC50 Rat (4 hours): 7.4 mg/l
Acute oral toxicity	LD50 Rat: 300 - 2,000 mg/kg

n-Butanol

Skin corrosion/irritation	Primary irritation (Rabbit): 24 hours; 1.4 (Max. score is 8.0.)
Serious eye damage/eye irritation	Primary irritation (Rabbit): 27.3 (Max. score is 110.)
Respiratory or skin sensitisation	No data available
Germ cell mutagenicity	Genotoxicity in vitro: No data available Genotoxicity in vivo: No data available Assessment Mutagenicity: No data available
Reproductive toxicity	Reproductive toxicity: No data available Assessment Reproductive toxicity: No data available Teratogenicity: No data available Assessment teratogenicity: No data available
STOT - single exposure	No data available
STOT - repeated exposure	No data available
Aspiration toxicity	No data available
Carcinogenicity	Assessment carcinogenicity: Contains no ingredient listed as a carcinogen

SECTION 12 ECOLOGICAL INFORMATION

Aquatic toxicity Non-toxic to aquatic life.

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)) 96 hours: 1,376 mg/l

n-Butanol

Toxicity to aquatic invertebrates	EC50 (Daphnia magna (Water flea)) 48 hours: 1,328 mg/l
Toxicity to algae	ErC50 (Pseudokirchneriella subcapitata (green algae)) 96 hours: 225 mg/l
Chronic toxicity to fish	No data available
Chronic toxicity to aquatic invertebrates	No data available
Biodegradation	Readily biodegradable. Closed Bottle test (20 d): 92 %
Bioaccumulative potential	No data available
Mobility in soil	No data available
Other adverse effects	No data available

SECTION 13 DISPOSAL CONSIDERATIONS

Waste Code	D001 - Ignitability (RQ 100 LB). Re-evaluation of the product may be required by the user at the time of disposal, since the product uses, transformations, mixtures, contamination, and spillage may change the classification.
Disposal methods	Land disposal of this product is restricted. Dispose of only in accordance with local, state, and federal regulations. Do not contaminate any lakes, streams, ponds, groundwater or soil.
Empty containers.	Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH. Empty drums should be completely drained, triple-rinsed, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

SECTION 14 TRANSPORT INFORMATION

DOT	UN 1120, Butanols, 3, III When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.
------------	-------------------------------------------------------------------------------------------------------------------------------

n-Butanol

IATA UN 1120, Butanols, 3, III
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

IMDG UN 1120, Butanols, 3, III
When shipped in quantities greater than 5,000 lbs, RQ must be added to the shipping description.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Remarks No data available

SECTION 15 REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA Inventory Listing

Components

1-Butanol

CAS-No.

71-36-3

SARA 302 Status

Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

CAS-No.

Weight percent

SARA 311/312 Classification

"Immediate (acute) health hazard", "Fire hazard"

SARA 313 Chemical

Components

1-Butanol

CAS-No.

71-36-3

Weight percent

>= 99 %

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Components

1-Butanol

Reportable Quantity

5,000 LB

Weight percent

>= 99 %

n-Butanol

INTERNATIONAL REGULATIONS

WHMIS Classification

Flammable liquids	Category 3
Acute toxicity (Oral)	Category 4
Serious eye damage	Category 1
Skin irritation	Category 2
Specific target organ toxicity - single exposure	Category 3 (Narcotic effects)
Specific target organ toxicity - single exposure	Category 3 (Resp. irritation)

European Union

Classification according to Regulation (EU) 1272/2008.

Flammable liquids, Category 3
 Acute toxicity (Oral), Category 4
 Serious eye damage, Category 1
 Skin irritation, Category 2
 Specific target organ toxicity - single exposure, Category 3 (Narcotic effects)
 Specific target organ toxicity - single exposure, Category 3 (Resp. irritation)

Australia. Inventory of Chemical Substances (AICS)	Listed
Japan. Inventory of Existing and New Chemical Substances (ENCS)	Listed
Japan. ISHL - Inventory of Chemical Substances	Listed
Canada. Domestic Substances List (DSL) Inventory	Listed
Canada. Non-Domestic Substance Listing (NDSL)	Not listed
Philippines. Inventory of Chemicals / Chemical Substances (PICCS)	Listed
Korea. Existing Chemicals Inventory (KECI)	Listed
China. Inventory of Existing Chemical Substances (IECSC)	Listed
Mexico	Listed
New Zealand. Inventory of Chemical Substances	Listed
Switzerland	Listed
Taiwan. National Existing Chemical Inventory (NECI)	Listed

n-Butanol

Please note: The names and CAS numbers which are used for this product in the stated inventories may deviate from the information which is listed in Section 3.

STATE REGULATIONS

California Prop. 65

Components

none

CAS-No.**SECTION 16 OTHER INFORMATION**

HAZARD RATINGS

	<u>Health</u>	<u>Flammability</u>	<u>Physical Hazard/ Instability</u>
HMIS®	3	2	0
NFPA	3	2	0

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR SASOL CHEMICALS (USA) LLC'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH SASOL CHEMICALS (USA) LLC CONSIDERS ACCURATE AND RELIABLE, SASOL CHEMICALS (USA) LLC MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.
