

# Emergency Response Information

---

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Trade name</b>	PARAFOL® 12-97	
<b>Synonyms</b>	C12 Paraffin, Dodecane	
<b>Manufacturer/Supplier</b>	Sasol Chemicals (USA) LLC	
<b>Address</b>	12120 Wickchester Lane Houston TX 77079	
<b>Telephone</b>	CHEMTREC North America Transportation Emergency (24-hr)	(800) 424-9300
	CHEMTREC World Wide	(703) 527-3887
	Other Emergencies (24-hr)	(337) 494-5142

---

## SECTION 2. SHIPPING DESCRIPTION

<b>DOT</b>	NA 1993, Combustible liquid, n.o.s.(Dodecane), III This product is regulated as a hazardous material according to the Department of Transportation only in bulk quantities (greater than 119 gallons per package).
------------	---

---

## SECTION 3. POTENTIAL HAZARDS

<b>Appearance</b>	Clear, colorless liquid	<b>Odour</b>	Hydrocarbons
<b>GHS Classification</b>	Flammable liquids, Category 4; Aspiration hazard, Category 1;		
<b>Signal word</b>	Danger		
<b>Hazard statements</b>	Combustible liquid. May be fatal if swallowed and enters airways.		
<b>Precautionary statements</b>	Keep away from open flames/hot surfaces. - No smoking. Wear protective gloves/ eye protection/ face protection. In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide for extinction. IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. Store locked up in a well-ventilated place. Keep cool. Dispose of contents/ container to an approved waste disposal plant.		

---

## SECTION 4. FIRST AID MEASURES

<b>Eye contact</b>	Rinse immediately with plenty of water for at least 15 minutes. If eye irritation persists, consult a specialist.
<b>Skin contact</b>	If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Consult a physician.

---

## SECTION 5. FIRE AND EXPLOSION HAZARDS

<b>Flash point</b>	ca. 71 °C, 160 °F; DIN 51758;
<b>Auto-ignition temperature</b>	Not applicable
<b>Fire and explosion</b>	NFPA Class IIIA combustible liquid.
<b>Extinguishing media</b>	Water spray or fog, foam, dry chemical, CO2
<b>Fire fighting instructions</b>	In the event of fire, wear self-contained breathing apparatus.
<b>Further information</b>	Keep containers and surroundings cool with water spray.

---

## SECTION 6. SPILL AND RECOVERY MEASURES

<b>Steps to be taken in case of spill or leak</b>	Evacuate the area and eliminate all sources of ignition. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
<b>Spill precautions</b>	Avoid subsoil penetration. Do not flush into surface water or sanitary sewer system.

---

**THIS INFORMATION IS PROVIDED TO COMPLY WITH THE REQUIREMENTS OF 49 CFR 172.602. FOR ADDITIONAL PRODUCT INFORMATION, PLEASE REFER TO THE MATERIAL SAFETY DATA SHEET (MSDS).**

---