



Description

Sasol North America's ALFOL® Alcohols are blends of high purity petrochemical-based linear primary alcohols with even-numbered carbon chain lengths. ALFOL® 20+ Alcohol is a waxy solid with off-white coloring and a slight sweet odor.

ALFOL® Alcohols are physically and chemically equivalent to corresponding oleochemical-based alcohols derived from such sources as coconut oil and palm kernel oil.

Applications

ALFOL® 20+ Alcohol is used in the following applications:

- Lubricants for plastics, textiles and metals
- Ethoxylation and sulfation to prepare emulsifiers and biodegradable surfactants
- Defoamers for paper, latex and other aqueous slurries (FDA sanctioned CFR 21, § 176.210)
- Esters for plastic lubricants and lubricant additives
- Synthetic waxes and binders
- Water evaporation control
- Chemical intermediate for other derivatives

Properties

Typical physical properties are listed in the table to the right. Actual properties will vary from lot to lot.

Contact Information

For technical information:

Sasol North America

Product Steward

2201 Old Spanish Trail

Westlake, Louisiana 70669

Telephone: (337)494-4133

Fax: (281)368-0819

TDS.ProductSteward@us.sasol.com

For sales and pricing information contact a sales representative at:

Sasol North America

900 Threadneedle

Houston, TX 77079-2990

Telephone: (281)588-3000

Fax: (281)368-1531

info@us.sasol.com

Typical Properties	ALFOL® 20+
Average molecular wt.	323
Total Alcohol, wt. %	≥80
Homolog Distribution, wt. %	
C18OH & Lower	< 5
C20OH	30 – 60
C22OH	15 – 35
C24OH	10 – 20
C26OH & Higher	< 20
Water, wt. %	< 0.1
Hydroxyl number, mg KOH/g	120 – 170
Specific gravity, g/cc @ 75°C	0.815
Flash point, °C, (°F)	199 (390)
Melting Point, °C, (°F)	45 – 54 (113 – 139)
Boiling Point, °C, (°F)	343 (650)
Viscosity cSt @ 99°C	5.3
Appearance, room temperature	Off-white solid
Vapor Pressure, mmHg @ 21 °C	0.13 mmHg
Vapor Density, Air = 1	10.3 – 14.1

ALFOL is a registered trademark of Sasol North America Inc.

The preceding data is based on tests and experience, which Sasol North America believes reliable, and is supplied for informational purposes only. Sasol North America expressly disclaims any liability whatsoever for damage or injury which results from the use of the preceding data and nothing contained therein shall constitute a guarantee, warranty, or representation (including freedom from patent liability) by Sasol North America with respect to the data, the product described, or its fitness for use for any specific purpose, even if that purpose is known to Sasol North America.

For detailed safety and handling information regarding these products, please refer to the respective Sasol North America Material Safety Data Sheet.